



\*Depending on the print head.  
KLONER3D<sup>®</sup> 3D PRINTERS MADE ENTIRELY IN ITALY

## TECHNICAL SPECIFICATIONS

|  |   |
|--|---|
| EXTERNAL DIMENSIONS (WxDxH)                          | 690x460x600mm   |
| WEIGHT   | 35Kg  |
| PRINT AREA (XYZ)                                     | 500x240x140mm (16,80 lt)  |
| INTERCHANGEABLE HEAD                                 | YES   |
| DUAL EXTRUDER  | YES*  |
| FILAMENT DIAMETER                                    | 3mm-1,75mm*   |
| NOZZLE DIAMETER                                      | 0,5 (0,3*-0,8*)mm   |
| MIN. LAYER HEIGHT                                    | 0,035*-0,05mm   |
| HEATED PRINTER BED                                   | YES   |
| CLOSED PRINTING ENVIRONMENT                          | YES   |
| PRINTER BED ADJUSTMENT                               | NO  |
| MECHANICAL MOVEMENT                                  | TBMS  |
| MOVEMENT RESOLUTION                                  | 0,01mm  |
| POSITIONING RESOLUTION                               | 0,01mm  |
| BACKLASH CONTROL                                     | YES   |
| MECHANICAL ADJUSTMENT, MAINTENANCE, LUBRICATION ETC. | NO  |
| PRINTABLE MATERIALS                                  | MULTIMATERIAL   |
| OPERATING SYSTEM OF THE CUSTOMER                     | Windows, Mac and Linux  |
| INPUT FILE FORMATS                                   | STL, OBJ, GCODE   |
| OPERATING REQUIREMENTS                               | <u>electrical</u> : 100-240 Vac 50-60 Hz; ~400W<br><u>operation</u> : temperature: 15°C-35°C; humidity: 15%-55% |

CASE COLOR



the box modular system  
a system endless possibilities

For further information:

KLONER3D<sup>®</sup>  
firenze - italy  
tel. +39(0)55 66 43 96  
fax. +39(0)55 398 0810

www.kloner3d.com  
info@kloner3d.com  
sales@kloner3d.com

designed by:  
clevertex & AI  
info@clevertex.eu

produced by:  
officine verdelli  
tel. +39(0)55 66 05 92